















Single-axis actuator inquiry sheet										
Customer		Register date		Register person						
Needs	Stroke (mm)									
	Speed (mm/s)									
	Payload (kg)									
	Repeatability accuracy (mm)	<input type="checkbox"/> ±0.1 <input type="checkbox"/> ±0.05 <input type="checkbox"/> ±0.02 <input type="checkbox"/> ±0.01								
	Work piece moment (mm)									
	A	B	C	A	B	C	A	C		
Motor brand	Motor model No.									
Motor combination	<input type="checkbox"/> M  <input type="checkbox"/> BC  <input type="checkbox"/> BR  <input type="checkbox"/> BL  <input type="checkbox"/> BM  <input type="checkbox"/> L  <input type="checkbox"/> LU  <input type="checkbox"/> LD  <input type="checkbox"/> R  <input type="checkbox"/> RU  <input type="checkbox"/> RD 									
SENSOR connect method	<input type="checkbox"/> Inside <input type="checkbox"/> Outside									
Application	<input type="checkbox"/> Pick&Place <input type="checkbox"/> Processing work <input type="checkbox"/> CCD Testing <input type="checkbox"/> Position test <input type="checkbox"/> Screw fastening <input type="checkbox"/> Moving test <input type="checkbox"/> Dispenser <input type="checkbox"/> Other					Figure				
Usage environment	<input type="checkbox"/> Clean room(Class)		Class 10	Class 100	Class 1000	Remarks				
	<input type="checkbox"/> General environment									
Noise request	<input type="checkbox"/> No request <input type="checkbox"/> 70~80 Decibel <input type="checkbox"/> 60~70 Decibel (Decibel level will influence price)									
Ball screw brand	<input type="checkbox"/> Standard type(M.I.T)		Request brand			(Will influence price)				
Equipment For	<input type="checkbox"/> Mass production <input type="checkbox"/> Trial run									
Remarks										

※ Fill out the form and contact the nearest Mindman sales office or distributor.

Inquiry sheet

SLIDER ELECTRIC CYLINDER - BALL SCREW DRIVE (WITHOUT MOTOR)



Multi-axis actuator inquiry sheet							
Customer		Register date			Register person		
Needs	Stroke (mm)	X		Y		Z	
	Speed (mm/s)	X		Y		Z	
	Payload (kg)						
	Repeatability accuracy (mm)	<input type="checkbox"/> ±0.1 <input type="checkbox"/> ±0.05 <input type="checkbox"/> ±0.02 <input type="checkbox"/> ±0.01					
Work piece moment (mm)							
	A	B	C	A	B	C	A C
Combination types	A type	<input type="checkbox"/> A1	<input type="checkbox"/> A2	<input type="checkbox"/> A3	<input type="checkbox"/> A4		
	G type	<input type="checkbox"/> G1	<input type="checkbox"/> G2	<input type="checkbox"/> G3	<input type="checkbox"/> G4		
	P type	<input type="checkbox"/> P1	<input type="checkbox"/> P2				
	F type	<input type="checkbox"/> F1	<input type="checkbox"/> F2				
Motor brand	Motor model No.						
Motor combination	X axis	<input type="checkbox"/> M	<input type="checkbox"/> BC	<input type="checkbox"/> BR	<input type="checkbox"/> BL	<input type="checkbox"/> BM	
		<input type="checkbox"/> L	<input type="checkbox"/> LU	<input type="checkbox"/> LD			
		<input type="checkbox"/> R	<input type="checkbox"/> RU	<input type="checkbox"/> RD			
	Y axis	<input type="checkbox"/> M	<input type="checkbox"/> BC	<input type="checkbox"/> BR	<input type="checkbox"/> BL	<input type="checkbox"/> BM	
		<input type="checkbox"/> L	<input type="checkbox"/> LU	<input type="checkbox"/> LD			
		<input type="checkbox"/> R	<input type="checkbox"/> RU	<input type="checkbox"/> RD			
	Z axis	<input type="checkbox"/> M	<input type="checkbox"/> BC	<input type="checkbox"/> BR	<input type="checkbox"/> BL	<input type="checkbox"/> BM	
SENSOR Connect method	<input type="checkbox"/> Inside <input type="checkbox"/> Outside						
Application	<input type="checkbox"/> Pick&Place <input type="checkbox"/> Position test <input type="checkbox"/> Processing work <input type="checkbox"/> Screw fastening <input type="checkbox"/> CCD Testing <input type="checkbox"/> Moving test <input type="checkbox"/> Dispenser						
If Y-axis is longer than stroke 350mm, support is suggested to add.							
Usage environment	<input type="checkbox"/> Dusty environment <input type="checkbox"/> General environment <input type="checkbox"/> Clean room(Class)				Class 10	Class 100	Class 1000
Noise request	<input type="checkbox"/> No request <input type="checkbox"/> 70~80 Decibel <input type="checkbox"/> 60~70 Decibel				(Decibel level will influence price)		
Ball screw brand	<input type="checkbox"/> Standard type (M.I.T)		Request brand		(Will influence price)		
Equipment for	<input type="checkbox"/> Mass production <input type="checkbox"/> Trial run						
Remarks							

※ Fill out the form and contact the nearest Mindman sales office or distributor.